


# Outdoor OH Optical Cable 144 Core with messenger(GYFTC8S)

## product structure diagram



## construction

1. Colored fiber  
Coated outside diameter: 125.0±0.1um  
Optical fiber diameter: 242±7um  
UV color fiber: Standard chromatogram  
-Blue, Orange, Green, Brown, Gray/Slate, White, Red, Black, Yellow, Violet, Rose/Pink, Aqua
  2. Tube filling compound(Gel)
  3. PBT loose tube
  4. FRP strengthen centre member
  5. Water Blocking tape
  6. Steel wire strand wire
  7. Steel tape
  8. Ripcord
  9. Black PE out jacket
- Outside diameter: 14.5\*21.5±0.5mm

## parameters of fiber

Optical fiber type	Unit	SM G652D	SM G657A2	MM 50/125	MM 62.5/125	MM OM3-300
Waveband	nm	1310/1550	1310/1550	850/1300	850/1300	850/1300
Attenuation	dB/km	0.36/0.23	0.36/0.23	3.0/1.0	3.0/1.0	3.0/1.0

## Product parameters

Performance	Long-term	Short-term
Max. Tension (N)	1200	4000
Max. Crushing Resistance(N/100mm <sup>2</sup> )	800	1500
Min. Bending Radius	30D	15D
Storage and operating temperature	-40°C - +70°C	

## Appearance and packaging

1. No damage on the surface; no trachoma.
2. Wooden tray packaging; wood whole seal packaging
3. Segment length: no less than 1000M. The segment length of each tray of the same batch shall be similar as much as possible. Other lengths can be agreed upon through consultation.
4. Report certificate: It includes optical cable inspection number, optical cable type, core number, optical fiber type, length, etc